	UTURO DA TINTA Code: 12640000	
/ersion	n: 1 Date of compilation: 21/11/2019	Date of printing: 21/11/2019
SECTIO	ON 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING	
1.1	PRODUCT IDENTIFIER: Microneuce SV 100 - Stucco Veneziano Code: 12640000	
1.2	RELEVANT IDENTIFIED USES OF THE SUBSTANCE OR MIXTURE AND USES ADVISED AGAINST:       [] Industrial [X] Provide the control of the c	ofessional [X] Consumers
	None. As there is not classified as dangerous, this product can be used in ways other than the identified uses, but all uses have to be co with the safety guidelines provided. <u>Restrictions on manufacture, placing on market and use, according to Annex XVII of Regulation (EC) No. 1907/2006</u>	onsistent
1.3	DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET: NEUCE - Indústria de Tintas, S.A. Rua Francisco Rocha - Aptdo. 4514 - 3700-892 - Romariz SJM (Portugal) Phone: + 351 256 840040 - Fax: + 351 256 840049 <u>E-mail address of the person responsible for the Safety Data Sheet:</u> e-mail: geral@neuce.pt	
1.4	EMERGENCY TELEPHONE NUMBER: +351 256 840041 (9:00-18:30 h.) (working hours)	
SECTIO	ON 2 : HAZARDS IDENTIFICATION	
2.1	CLASSIFICATION OF THE SUBSTANCE OR MIXTURE: This product is not classified as dangerous, in accordance with Regulation (EU) No. 1272/2008~2018/1480 (CLP)	
	Note: When in section 3 a range of percentages is used, the health and environmental hazards describe the effects of the highest conce of each component, but below the maximum value.	ntration
	Note: This product does not require a Safety Data Sheet according to the Regulation (EC) no. 2015/830. When used as recommended or ordinary conditions, it should not present a physicochemical, health safety or environmental hazard. However, an MSDS can be provide courtesy in response to a customer request.	
2.2	LABEL ELEMENTS:         This product does not require pictograms, in accordance with Reg J ation (EJ) No.1272/2008~2018/1480 (CLP)         Hazard statements:         None.         Precautionary statements:         P102       Keep out of reach of children.         P271       Use only outdoors or in a well-ventilated area.         P280B       Wear protective gloves and eye protection .         P273       Avoid release to the environment.	
	Supplementary statements:         BUH 208         Contains mixture CIT EC 247-500-7 MIT EC 220-239-6 (3:1). May produce an allergic reaction.         EUH 210       Safety data sheet available on request.         Substances that contribute to classification:         Mixture CIT EC 247-500-7 MIT EC 220-239-6 (3:1)	
2.3	OTHER HAZARDS: Hazards which do not result in classification but which may contribute to the overall hazards of the mixture: Other physicochemical hazards: potentially flammable or explosive. Other adverse human health effects: No other relevant adverse effects are known. Other negative environmental effects: Does not contain substances that fulfil the PBT/vPvB criteria.	mixture

Date of compilation: 21/11/2019

Page 2/10

	VEUCE	Microneuce SV 100 - Stucco Veneziano Code: 12640000	
SECTIO	ON 3 : COMPOS	ITION/INFORMATION ON INGREDIENTS	
3.1	SUBSTANCES : Not applicable	mixture).	
3.2	HAZARDOUS I	<u>iption:</u> ients, extenders, resins and additives in aqueous media.	
	< 0,5 %	Naphtha (petroleum), hydrodesulfurized heavy CAS: 64742-82-1, EC: 265-185-4 CLP: Danger: Flam. Liq. 3:H226   Skin Irrit. 2:H315   STOT SE ( nar cos is ) 3 Asp. Tox. 1:H304   Aquatic Chronic 2:H411	Index No. 649-330-00-2 H336   (Note H,P) < ATP01
	0,1 < 0,3 %	Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) (CAS: 64742-82-1), List No. 919-446-0 REACH: 01- CLP: Danger: Flam. Liq. 3:H226   STOT SE (nar cosis) 3:H336   STOT RE 1:H Tox. 1:H304   Aquatic Chronic 2:H411   EUH066	-2119458049-33 Autoclassified H372i   Asp. < REACH
	< 0,0015 %	Reaction mass of 5-chloro-2-methyl-2H-isothiazolin-3-one [EC 247-500-7]	and 2-methyl-2H-isothiazol-3-one [EC 220-239-6]
		(3:1) CAS: 55965-84-9, List No. 611-341-5 CLP: Danger: Acute Tox. (inh.) 2:H330   Acute Tox. (s ki n) 2:H310   Acute To 3:H301   Skin Corr. 1C:H314   Eye Dam. 1:H318   Skin Sens. 1A:H317   Aq 1:H400 (M=10)   Aquatic Chronic 1:H410 (M=10)   EUH071	
	<u>Stabilizers:</u> None <u>Reference to ot</u>	in other components or impurities which will influence the classification of the pr <u>her sections:</u> nation, see sections 8, 11, 12 and 16.	oduct.
		DF VERY HIGH CONCERN (SVHC):	
	Substances SV	ECHA on 15/01/2019. HC subject to authorisation, included in Annex XIV of Regulation (EC) no. 1907/20	1 <u>06:</u>
	None <u>Substances SV</u> None	HC candidate to be included in Annex XIV of Regulation (EC) no. 1907/2006:	
		CUMULABLE AND TOXIC PBT, OR VERY PERSISTENT AND VERY BIOACCUMULABLE VPVB SUBSTANC in substances that fulfil the PBT/VPVB criteria.	<u>5:</u>
SECTI	ON 4 : FIRST A	ID MEASURES	
4.1	DESCRIPTION	OF FIRST-AID MEASURES:	
		Symptoms may occur after exposure, so that in case of direct exposure to the pro eek medical attention. Never give anything by mouth to an unconscious person.	duct, when in doubt, or when symptoms persist,
	Route of exposi	ire Symptoms and effects, acute and delayed	Description of first-aid measures
	Inhalation:	Usually produces no symptoms.	Should there be any symptoms, transfer the person affected to the open air.
	<u>Skin:</u>	Usually produces no symptoms.	Remove contaminated clothing. Wash thoroughly the affected area with plenty of cold or lukewarm water and neutral soap, or use a suitable skin cleanser. Do not use solvents or thinners.
	<u>Eyes:</u>	Usually produces no symptoms.	Remove contact lenses. Rinse eyes copiously by irrigation with plenty of clean, fresh water, holding the eyelids apart. If irritation persists, consult a physician.
	Ingestion:	If swallowed in high doses, may cause gastrointestinal disturbances.	If swallowed, seek immediate medical attention. Do not induce vomiting, due to the risk of aspiration. Keep the patient at rest.
4.2		ANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED: toms and effects are indicated in sections 4.1 and 11.1	
4.3	INDICATION O	F ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED: ian: Treatment should be directed at the control of symptoms and the clinical co ontraindications: Specific antidote not known.	ondition of the patient.

Date of compilation: 21/11/2019

Page 3/10

	<b>VEUCE</b>	Microneuce SV 100 - Stucco Veneziano Code: 12640000	
SECTI	ON 5 : FIRE-FIG	GHTING MEASURES	
5.1		<u>NG MEDIA :</u> wwder or CO2. In the case of more important fires, also alcohol resistant foam and water spray/mist. Do not use for direct water jet. Direct water jet may not be effective to extinguish the fire, since the fire may spread.	
5.2	As consequence	IRDS ARISING FROM THE SUBSTANCE OR MIXTURE : re of combustion or thermal decomposition, hazardous products may be produced: carbon monoxide, carbon dioxide. Exposure to decomposition products may be a hazard to health.	
5.3	apparatus, glov combat fire from Other recomme	IREFIGHTERS: ive equipment: Depending on magnitude of fire, heat-proof protective clothing may be required, appropriate independent breathing ves, protective glasses or face masks and boots. If the fire-proof protective equipment is not available or is not being us ed, m a sheltered position or from a safe distance. The standard EN469 provides a basic level of protection for chemical incidents. endations: Cool with water the tanks, cisterns or containers close to sources of heat or fire. Bear in mind the direction of the wind. re-fighting residue to enter drains, sewers or water courses.	
SECTI	ON 6 : ACCIDEN	NTAL RELEASE MEASURES	
6.1	Eliminate possi	<u>CCAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES:</u> ible sources of ignition and when appropriate, ventilate the area. Do not smoke. Avoid direct contact with this product. Avoid urs. Keep people without protection in opposition to the wind direction.	
6.2	Avoid contamin	AL RECAUTIONS: nation of drains, surface or subterranean water and soil. In the case of large scale spills or when the product contaminates lakes, ges, inform the appropriate authorities in accordance with local regulations.	
6.3	Contain and mo	D MATERIAL FOR CONTAINMENT AND CLEANING UP: op up spills with non-combustible absorbent materials (earth, sand, vermiculite, diatomaceous earth, etc). Avoid use of solvents. ins in a closed container.	
6.4	For contact info For information For exposure co	OTHER SECTIONS: ormation in case of emergency, see section 1. n on safe handling, see section 7. ontrols and personal protection measures, see section 8. osal, follow the recommendations in section 13.	
SECTI	ON 7 : HANDLI	NG AND STORAGE	
7.1	Comply with th General recommunity Use in areas free container tightll Recommendatii Vapours are he distant ignition and other source tools with a pot Recommendatii Do not eat, drir protection mea Recommendati	ee from sources of ignition and away from heat or electrical sources. Do not smoke. Avoid any type of leakage or escape. Keep the	
7.2	Forbid the entry Do not smoke i closed carefully <u>Class of storage</u> <u>Maximum stora</u> <u>Temperature int</u> <u>Incompatible m</u> Keep away from <u>Type of packagin</u> According to cu Limit quantity (	age period       : 12. months         terval       : min: 5. °C, max: 35. °C (recommended).         naterials:       : moxidixing agents, from strongly alkaline and strongly acid materials.	
7.3	SPECIFIC END For the use of t	USES: This product do not exist particular recommendations apart from that already indicated.	

Date of compilation: 21/11/2019

ION 8 : EXPOSURE CONTROLS/PERSONAL PROTECT	ION							
CONTROL PARAMETERS: If a product contains ingredients with exposure limits, ma effectiveness of the ventilation or other control measures made to EN689, EN14042 and EN482 standard concerning chemical and biological agents. Reference should be also substances.	and/or the necessity to use respiratory protective methods for assesing the exposure by inhalation to	e equipment. Reference s hould be o chemical agents, and exposure	to					
OCCUPATIONAL EXPOSURE LIMIT VALUES (TLV)								
AGCIH 2018 Naphtha (petroleum), hydrodesulfurized heavy Hydrocarbons C9-C12 (aromatics 2-25%) Mixture CIT EC 247-500-7 MIT EC 220-239-6 (3:1)	<u>Year</u> <u>ppm</u> mg/m3 100. 525. 100 - 0.080	TLV-STEL ppm mg/m3  - 0.23	Remarks Recommended Recommended					
TLV - Threshold Limit Value, TWA - Time Weighted Averag	e, STEL - Short Term Exposure Limit.		1					
REACH. DNEL values may differ from a occupational expos	BIOLOGICAL LIMIT VALUES: Not available DERIVED NO-EFFECT LEVEL (DNEL): Derived no-effect level (DNEL) is a level of exposure that is considered safe, derived from toxicity data according to specific guidances included in REACH. DNEL values may differ from a occupational exposure limit (OEL) for the same chemical. OEL values may come recommended by a particular company, a government regulatory agency or an organization of experts. Although considered protective of health, the OEL values are							
Derived by a process and rai to the term - Systemic effects, acute and chronic: Hydrocarbons C9-C12 (aromatics 2-25%) Mixture CIT EC 247-500-7 MIT EC 220-239-6 (3:1)	DNEL Inhalation mg/m3 570. (a) 330. ( - (a) - (c							
Derived no-effect level, workers: - Local effects, acute and chronic: Hydrocarbons C9-C12 (aromatics 2-25%) Mixture CIT EC 247-500-7 MIT EC 220-239-6 (3:1)	DNEL Inhalation mg/m3 s/r (a) s/r (c - (a) - (c		DNEL Eyes mg/cm2 s/r (a) - (a)					
Derived no-effect level, general population: - Systemic effects, acute and chronic: Hydrocarbons C9-C12 (aromatics 2-25%) Mixture CIT EC 247-500-7 MIT EC 220-239-6 (3:1)	DNEL Inhalation mg/m3 570. (a) 71.0 ( - (a) - (d)		DNEL Oral mg/kg bw/d s/r (a) 21.0 - (a)					
Derived no-effect level, general population: - Local effects, acute and chronic: Hydrocarbons C9-C12 (aromatics 2-25%) Mixture CIT EC 247-500-7 MIT EC 220-239-6 (3:1)	DNEL Inhalation mg/m3 s/r (a) s/r (c) - (a) - (c)		DNEL Eyes mg/cm2 s/r (a) - (a)					
<ul> <li>(a) - Acute, short-term exposure, (c) - Chronic, long-term or repeated exposure.</li> <li>(-) - DNEL not available (without data of registration REACH).</li> <li>s/r - DNEL not derived (not identified hazard).</li> </ul> PREDICTED NO-EFFECT CONCENTRATION (PNEC):								
Predicted no-effect concentration, aquatic organisms: - Fresh water, marine water and intermittent release: Hydrocarbons C9-C12 (aromatics 2-25%) Mixture CIT EC 247-500-7 MIT EC 220-239-6 (3:1)	PNEC Fresh water mg/l uvcb	PNEC Marine mg/l uvcb	PNEC Intermittent mg/l uvcb -					
- Wastewater treatment plants (STP) and sediments in fi and marine water: Hydrocarbons C9-C12 (aromatics 2-25%) Mixture CIT EC 247-500-7 MIT EC 220-239-6 (3:1)	resh- mg/l uvcb	PNEC Sediments mg/kg dw/d uvcb	PNEC Sediments mg/kg dw/d uvcb -					
Predicted no-effect concentration, terrestrial organisms: - Air, soil and effects for predators and humans: Hydrocarbons C9-C12 (aromatics 2-25%) Mixture CIT EC 247-500-7 MIT EC 220-239-6 (3:1)	PNEC Air mg/m3 uvcb	PNEC Soil mg/kg dw/d uvcb	PNEC Oral mg/kg dw/d uvcb -					

O FUTURO DA TINTA	Microneuce SV 100 - Stucco Veneziano Code: 12640000							
EXPOSURE C	<u>ONTROLS:</u>							
ENGINEERIN	ENGINEERING MEASURES:							
	Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these measures are not sufficient to maintain concentrations of particulates and vapours below the Occupational Exposure Limits, suitable respiratory protection must be worn.							
Protection of Protection of	respiratory system: Avoid the inhalation of vapours. eyes and face: It is recommended to install water taps or sources with clean water close to the working area. hands and skin: It is recommended to install water taps or sources with clean water close to the working area. Barrier creams may help e exposed areas of the skin. Barrier creams should not be applied once exposure has occurred.							
As a general the correspo	<u>VAL EXPOSURE CONTROLS:</u> Regulation (EU) No. 2016/425: measure on prevention and safety in the work place, we recommend the use of a basic personal protection equipment (PPE), with nding marking. For more information on personal protective equipment (storage, use, cleaning maint enance, type and cs of the PPE, protection class, marking, category, CEN norm, etc), you should consult the informative brochures provided by the rs of PPE.							
Mask:	A-type filter mask (brown) for gases and vapours of organic compounds with a boil ingpoint higher than 65°C (EN14387). Class 1: low capacity up to 1000 ppm, Class 2: medium capacity up to 5000 ppm, Class 3: high capacity up to 10000 ppm. In order to obtain a suitable protection level, the filter class must be selected depending on the type and concentration of the contaminating agents present, in accordance with the specifications supplied by the filter producers.							
Safety goggle	Safety goggles designed to protect against liquid splashes, with suitable lateral protection (EN166). Clean daily and disinfect at regular intervals in accordance with the instructions of the manufacturer.							
Face shield:	No.							
Gloves:	Gloves resistant against chemicals (EN374). When repeated or prolonged contact with the product is expected, gloves of protection level 5 or higher should be used, with a breakthrough time of >240 min. When short contact with the product is expected, use gloves with a protection level 2 or higher should be used, with a breakthrough time >30 min. The breakthrough time of the selected glove material should be in accordance with the pretended period of use. There are several factors (for example, temperature), they do in practice the period of use of a protective gloves resistant against chemicals is clearly lower than the established standard EN374. Due to the wide variety of circumstances and possibilities, the instructions/specifications provided by the glove supplier should be taken into account. The gloves should be immediately replaced when any sign of degradation is noted.							
Boots:	No.							
Apron:	No.							
Clothing:	No.							
ENVIRONME	ards: le (the product is handled at room temperature). <u>NTAL_EXPOSURE CO NTROLS:</u> illage in the environment. Avoid any release i nto the at mosphere.							
, ,	soil: Prevent contamination of soil.							
- Water Mar	er: Do not allow to escape into drains, sewers or water courses. agement Act: This product does not contain any substance included in the list of priority substances in the field of water policy under 00/60/EC~2013/39/EU.							
atmosphere. - <u>VOC (prod</u> organic solve water-borne. - <u>VOC (indu</u>	atmosphere:       Because of volatility, emissions to the atmosphere while handling and use may result. Avoid any release into the         uct ready for use*):       It is applicable the Directive 2004/42/EC, on the limitation of emissions of volatile compounds due to the use of ents: PAINTS AND VARNISHES (defined in the Directive 2004/42/EC, Amex I.1): Emission subcategory k) Multicd oured coating,         . (VOC max. 100. g/l* starting from 01.01.2010).       strial installations):         . If this product is used in an industrial installation, it must be verified if it is applicable the Directive 2010/75/EC, on of emissions of volatile compounds due to the use of organic solvents in certain activities and installations:							
1								

Date of compilation: 21/11/2019

	NEUCE FUTURO DA TINTA Microneuce SV 100 - Stucco Venezia Code: 12640000				
SECTI	ION 9 : PHYSICAL AND CHEMICAL PROPERTIES				
9.1	INFORMATIONON BASIC PHYSICAL AND CHEMICAL PROPE         Appearance         - Physical state         - Colour         - Odour threshold         pH-value         - pH         Change of state         - Melting point         - Initial boiling point         Density         - Vapour density         - Relative density         Stability         - Decomposition temperature         Viscosity:         - Dynamic viscosity         - Kinematic viscosity         - Kinematic viscosity         - Kinematic viscosity         - Vapour pressure         - Vapour pressure         - Vapour pressure         - Solubility in water:         - Liposolubility         - Partition coefficient: n-octanol/water         Hammability:         - Flash point         - Autoignition temperature         Explosive properties:         Vapour can form explosive mixtures with air and are able to Oxidizing properties:			at 20°C °C at 760 mmHg at 20/4°C Cps 20°C mm2/s at 40°C cSt 20°C nBuAc=100 25°C mmHg at 20°C kPa at 50°C e untested). ire). ain combustion).	Relative water Relative
9.2	Not classified as oxidizing product.           *Estimated values based on the substances composing the m           OTHER INFORMATION:           - Heat of combustion           - Solids	iixture. :	769*	Kcal/kg % Weight	
SECTI	<ul> <li>VOC (supply)</li> <li>The values indicated do not always coincide with product spectechnical data sheet. For additional information concerning ph and 12.</li> <li>ION 10 : STABILITY AND REACTIVITY</li> </ul>			cations can be found in the	
10.1	REACTIVITY: Corrosivity to metals: It is not corrosive to metals. Pyrophorical properties: It is not pyrophoric.				
10.2	CHEMICAL STAB ILI TY: Stable under recommended storage and handling conditions.				
10.3	POSSIBILITY OF HAZARDOUS REACTIONS: Possible dangerous reaction with oxidizing agents, acids.				
10.4	CONDITIONS TO AVOID: Heat: Keep away from sources of heat. Light: If possible, avoid direct contact with sunlight. Air: The product is not affected by exposure to air, but should a Pressure: Not relevant. Shock: The product is not sensitive to shocks, but as a record avoid dents and breakage of packaging, especially when the pro-	mmendation of a g	eneral nature should be	avoided bumps and rough h uring loading and download	nandling to operations.
10.5	INCOMPATIBLE MATERIALS: Keep away from oxidixing agents, from strongly alkaline and s	trongly acid mate	ials.		
10.6	HAZARDOUS DECOMPOSITION PRODUCTS: As consequence of thermal decomposition, hazardous product	ts may be produce	d: carbon monoxide.		

Date of compilation: 21/11/2019

Page 7/10

ION 11 : TOXICOLOGICAL INFORMA	TION							
perimental toxicological data on the prepar	ation is available. The toxic o	loqical dassi	fication for these mixture has b	peen carried out by using the				
ntional calculation method of the Regulatio	rimental toxicological data on the preparation is available. The toxic d og cal d æs ific at ion for t hes e mixt ure hæ been carried out by using the onal calculation method of the Regulation (EU) No. 1272/2008~2018/1480 (CLP).							
INFORMATIONON TOXICOLOGICAL	FFECTS:							
ACUTE TOXICITY:					_			
Dose and lethal concentrations			LD50 (OECD 401)	LD 50 (OECD 402)	LC50 (OECD 40			
for individual ingredients : Naphtha (petroleum), hydrodesulfurized heavy			mg/kg bw oral 6000. Rat	mg/kg bw cutaneous 3000. Rat	mg/m3·4h inhalation > 7630. Rat			
Hydrocarbons C9-C12 (aromatics 2-25%) Mixture CIT EC 247-500-7 MIT EC 220-239-6 (3:1)			> 5000. Rat 75. Rat	> 2000. Rabbit 140. Rat	> 13100. Rat > 1230. Rat			
			ATE	ATE	ATE			
for individual ingredients :				mg/kg bw cutaneous	mg/m3·4h inhalation			
Mixture CIT EC 247-500-7 MIT EC 220-2	239-6 (3:1)		75.	140.	50.* Du			
(*) - Point estimates of acute toxicity of used in the calculation of the ATE for cla	corresponding to the classific	cation catego	ry (see GHS/CLP Table 3.1.2).	These values are designed to be est results	9			
(-) - The components that are assumed	to have no acute toxicity at	the upper th	reshold of category 4 for the co	prresponding exposure route an	e			
ignored.								
No observed adverse effect level Not available								
Lowest observed adverse effect level Not available	Lowest observed adverse effect level							
INFORMATIONON LIKELY ROUTES OF								
			N		Criter			
Routes of exposure	Acute toxicity	Cat.		Main effects, acute and/or delayed				
Inhalation: Not classified	ATE > 20000 mg/m3	-	Not classified as a product v (based on available data, the	vith acute toxicity if inhaled e classification criteria are not	GHS/0 3.1.3.0			
			met).					
Skin:	ATE > 2000	-	Not classified as a product with acute toxicity in contact with					
Not classified	mg/kg bw		skin (based on available data, the classification criteria are not met).					
Eyes:	Not available	-	Not classified as a product with acute toxicity by eye contact					
Not classified			Not classified as a product with acute toxicity by eye contact (lack of data).					
Ingestion:	ATE > 2000	_	Not classified as a product v	vith acute toxicity if swallowed	d GHS/0			
Not classified	mg/kg bw		(based on available data, the	e classification criteria are not	3.1.3.0			
met).								
GHS/CLP 3.1.3.6: Classification of mixtures based on ingredients of the mixture (additivity formula).								
CORROSION / IRRITATION / SENSITISATION:								
Danger class	Target organs	Cat.	Main effects, acute and/or delayed					
Respirat or y corros ion/ir ritation	-	-	Not classified as a product corrosive or irritant by inhalation					
Not classified			het).	e classification criteria are not	1.2.6. 3.8.3.4			
Skin corrosion/irritation:	_	_	Not classified as a product o	orrosive or irritant in contact v	with GHS/0			
Not classified				a, the classification criteria are				
Contant and dense of the th	-	-		orrosive or irritant in contact w a, the classification criteria and				
Serious eye damage/irritation: Not classified		1	not met).					
Not classified Respiratory sensitisation:	-	-	Not classified as a product s		/			
Not classified	-	-	Not classified as a product s available data, the classifica		I on GHS/0 3.4.3.3			
Not classified Respiratory sensitisation:	-	-	available data, the classifica		3.4.3.			

GHS/CLP 3.3.3: Classification of the mixture when data are available for all components or only for some components. GHS/CLP 3.4.3.3: Classification of the mixture when data are available for all components or only for some components.

ADDITIONAL INFORMATION: Not available.

Date of compilation: 21/11/2019

Page 8/10

1									
Ę	DELAYED AND IMMEDIATE EFFECTS AS WELL AS CHRONIC EFFECTS FROM SHORT AND LONG-TERMEX POSURE: Routes of exposure: Not available.								
S	Short-term expo	<u>osure:</u> Not available. <u>peated exposure:</u> Not available.							
	INTERACTIVE EFFECTS: Not available.								
		A BOUT TOXICOCINETICS, METABOLISM	AND DISTRIBUTION	<u>:</u>					
		<u>ion:</u> Not available. <u>etics:</u> Not available.							
	ADDITIONAL IN	VFORMATION:							
	Not available.								
		cological data on the preparation as such is Iculation method of the Regulation (EU) No			e mixture has been car fied out	t by			
1 <u>T</u>	OXICITY:					_			
		naquatic environment		LC50 (OECD 203)	EC50 (OECD 202)		CD 201)		
N	or individual ing Naphtha (petrole	eum), hydrodesulfurized heavy		mg/l·96hours > 2.6 Fishes	mg/ŀ48hours > 2.3 Daphnia	mg/l·72hours > 10.			
⊢  M	Hydrocarbons C Mixture CIT EC 2	9-C12 (aromatics 2-25%) 247-500-7 MIT EC 220-239-6 (3:1)		> 10. Fishes 0.19 Fishes	> 10. Daphnia 0.16 Daphnia	> 4.6 0.018			
Ν	No observed effe	ect concentration			· ·	-1			
N	Vot available	d effect concentration							
	Not available								
A	ASSESSMENT O	OF AQUATIC TOXICITY:							
A	Aquatic toxicity		Cat.	Main hazards to the aquatic	environment		Criteria		
	<u>Acute aquatic to</u> Not classified	<u>ixicity:</u>	-	Not classified as a hazardou: aquatic life (based on availat are not met).	s product with acute toxicity to ole data, the classification crite	o eria	GHS/CLP 4.1.3.5.5		
	<u>Chronic aquatic t</u> Not classified	toxicity:	-	Not classified as a dangerou	s product with chronic toxicity effects (based on available dat e not met).	to a,	GHS/CLP 4.1.3.5.5		
	CLP 4.1.3.5.5.3: Classification of a mixture for acute hazards, based on summation of classified components.								
		Classification of a mixture for chronic (long	jterm) hazards, base	ed on summation of classified co	omponents.				
	PERSISTENCE A	ND DEGRADABILITY:							
	Aerobic biodegra	adation		DOO	%DBO/DQO	Biodegradabi	lity		
A	or individual ing			mgO2/g	5 days 14 days 28 days 24. 52. 74.	Easy	-		
fc						Easy			
ft N H	Naphtha (petrole Tydrocarbons C	eum), hydrodesulfurized heavy 29-C12 (aromatics 2-25%)							
ft N H M	Naphtha (petrole Tydrocarbons C Mixture CIT EC 2	eum), hydrodesulfurized heavy 9-C12 (aromatics 2-25%) 247-500-7 MIT EC 220-239-6 (3:1)	Ita from various hiblio	graphic sources		Innerenciy			
fc N H N	Naphtha (petrole Tydrocarbons C Mixture CIT EC 2 Note: Biodegrad	eum), hydrodesulfurized heavy 19-C12 (aromatics 2-25%) 247-500-7 MIT EC 220-239-6 (3:1) lability data correspond to an average of da	ita from various biblio	graphic sources.		Innerenciy			
fr N M N 3 <u>B</u>	Naphtha (petrole Tydrocarbons C Mixture CIT EC 2 Note: Biodegrad	eum), hydrodesulfurized heavy 9-C12 (aromatics 2-25%) 247-500-7 MIT EC 220-239-6 (3:1)	ata from various biblio	graphic sources.					
	Naphtha (petrole Hydrocarbons C Mixture CIT EC 2 Note: Biodegrad BIOACCUMULAT Not available. Bioaccumulatior	eum), hydrodesulfurized heavy 19-C12 (aromatics 2-25%) 247-500-7 MIT EC 220-239-6 (3:1) lability data correspond to an average of da TIVE POTENTIAL:	ata from various biblio	graphic sources.	BCF	Potential			
	Vaphtha (petrole Hydrocarbons C Mixture CIT EC 2 Note: Biodegrad BIOACCUMULAT Not available. Bioaccumulatior for individual ing Naphtha (petrole	eum), hydrodesulfurized heavy 9-C12 (aromatics 2-25%) 247-500-7 MIT EC 220-239-6 (3:1) lability data correspond to an average of da TIVE POTENTIAL: 	ata from various biblio	log Pow 5.65	L/kg > 100. (calculated)	Potential Not available			
in the second se	Naphtha (petrole tydrocarbons C vixture CIT EC 2 Note: Biodegrad <u>BIOACCUMULAT</u> Not available. <u>Bioaccumulation</u> br individual ing Naphtha (petrole tydrocarbons C	eum), hydrodesulfurized heavy 19-C12 (aromatics 2-25%) 247-500-7 MIT EC 220-239-6 (3:1) ability data correspond to an average of da <u>TIVE POTENTIAL:</u>	ata from various biblio	log Pow	L/kg	Potential	2		
	Vaphtha (petrole Hydrocarbons C Mixture CIT EC 2 Vote: Biodegrad BIOACCUMULAT Not available. Bioaccumulation for individual ing Vaphtha (petrole Hydrocarbons C Mixture CIT EC 2 MOBILITY IN SC	eum), hydrodesulfurized heavy 19-C12 (aromatics 2-25%) 247-500-7 MIT EC 220-239-6 (3:1) ability data correspond to an average of da TIVE POTENTIAL: 1 1 1 1 1 1 1 1 1 1 1 1 1	ata from various biblio	<u>loq Pow</u> 5.65 5.65	L/kg > 100. (calculated) > 100. (calculated)	Potential Not available Not available	2		
	Vaphtha (petrole tydrocarbons C vixture CIT EC 2 vote: Biodegrad <u>BIOACCUMULAT</u> vot available. <u>Bioaccumulation</u> or individual ing vaphtha (petrole tydrocarbons C vixture CIT EC 2 <u>MOBILITY IN SC</u> Vot available.	eum), hydrodesulfurized heavy 19-C12 (aromatics 2-25%) 247-500-7 MIT EC 220-239-6 (3:1) ability data correspond to an average of da TIVE POTENTIAL: 1 1 1 1 1 1 1 1 1 1 1 1 1	ata from various biblio	<u>log Pow</u> 5.65 5.65 -0.830	L/kg       > 100.     (calculated)       > 100.     (calculated)       3.2     (calculated)	Potential Not available Not available	2		
	Vaphtha (petrole Hydrocarbons C Hixture CIT EC 2 Vote: Biodegrad BIOACCUMULAT Not available. Bioaccumulation for individual ing Naphtha (petrole Hydrocarbons C MOBILITY IN SC Not available. Mobility for individual ing	eum), hydrodesulfurized heavy 19-C12 (aromatics 2-25%) 247-500-7 MIT EC 220-239-6 (3:1) tability data correspond to an average of da <u>TIVE POTENTIAL:</u> 0 0 0 0 0 0 0 0 0 0 0 0 0	ata from various biblio	log Pow 5.65 5.65 -0.830	L/kg > 100. (calculated) > 100. (calculated)	Potential Not available Not available Not available Potential	: 		
	Vaphtha (petrole tydrocarbons C vixture CIT EC 2 vote: Biodegrad <u>BIOACCUMULAT</u> vot available. <u>Bioaccumulation</u> or individual ing vaphtha (petrole tydrocarbons C <u>Vobility</u> or individual ing vaphtha (petrole tydrocarbons C	eum), hydrodesulfurized heavy 19-C12 (aromatics 2-25%) 247-500-7 MIT EC 220-239-6 (3:1) lability data correspond to an average of da TIVE POTENTIAL: 10 11/CE POTENTIAL: 12 12 12 12 12 12 12 12 12 12	ata from various biblio	log Pow 5.65 5.65 -0.830	L/kg       > 100.       (calculated)       3.2       (calculated)       Constant of Henry	Potential         Not available         Not available         Not available         Potential         Not available         Not available	2 2 		
	Vaphtha (petrole tydrocarbons C vixture CIT EC 2 vote: Biodegrad <u>BIOACCUMULAT</u> vot available. <u>Bioaccumulation</u> or individual ing vaphtha (petrole tydrocarbons C <u>Vobility</u> or individual ing vaphtha (petrole tydrocarbons C	eum), hydrodesulfurized heavy 19-C12 (aromatics 2-25%) 247-500-7 MIT EC 220-239-6 (3:1) lability data correspond to an average of da TIVE POTENTIAL: 1 1 1 1 1 1 1 1 1 1 1 1 1	ata from various biblio	log Pow 5.65 5.65 -0.830	L/kg       > 100.       (calculated)       3.2       (calculated)       Constant of Henry	Potential Not available Not available Not available Potential Not available	2 2 		
	Vaphtha (petrole tydrocarbons C vixture CIT EC 2 viture CIT EC 2 vote: Biodegrad BIOACCUMULAT vot available. Bioaccumulation or individual logenole tydrocarbons C vixture CIT EC 2 VIXture CIT EC 2 V	eum), hydrodesulfurized heavy 19-C12 (aromatics 2-25%) 247-500-7 MIT EC 220-239-6 (3:1) lability data correspond to an average of da TIVE POTENTIAL: 1 1 1 1 1 1 1 1 1 1 1 1 1	of Regulation (EC) no	log Pow 5.65 5.65 -0.830 log Koc 4.90 4.90 -1.22	L/kg       > 100.       (calculated)       3.2       (calculated)       Constant of Henry	Potential         Not available         Not available         Not available         Potential         Not available         Not available	2 2 		
	Vaphtha (petrole tydrocarbons C vixture CIT EC 2 viture CIT EC 2 vote: Biodegrad BIOACCUMULAT vot available. Bioaccumulation or individual ing vaphtha (petrole tydrocarbons C vixture CIT EC 2 VI available. Mobility or individual ing vaphtha (petrole tydrocarbons C vixture CIT EC 2 RESULTS OF PBT	eum), hydrodesulfurized heavy 19-C12 (aromatics 2-25%) 247-500-7 MIT EC 220-239-6 (3:1) lability data correspond to an average of da <u>TIVE POTENTIAL:</u> 10 11 12 12 12 12 12 12 12 12 12	of Regulation (EC) no	log Pow 5.65 5.65 -0.830 log Koc 4.90 4.90 -1.22	L/kg       > 100.       (calculated)       3.2       (calculated)       Constant of Henry	Potential         Not available         Not available         Not available         Potential         Not available         Not available	2 2 		
	Vaphtha (petrole tydrocarbons C vixture CIT EC 2 viture CIT EC 2 vote: Biodegrad BIOACCUMULAT vot available. Bioaccumulation or individual ing vaphtha (petrole tydrocarbons C vixture CIT EC 2 VI available. Mobility or individual ing vaphtha (petrole tydrocarbons C vixture CIT EC 2 RESULTS OF PBT	eum), hydrodesulfurized heavy 19-C12 (aromatics 2-25%) 247-500-7 MIT EC 220-239-6 (3:1) lability data correspond to an average of da TIVE POTENTIAL: 1 1 1 1 1 1 1 1 1 1 1 1 1	of Regulation (EC) no	log Pow 5.65 5.65 -0.830 log Koc 4.90 4.90 -1.22	L/kg       > 100.       (calculated)       3.2       (calculated)       Constant of Henry	Potential         Not available         Not available         Not available         Potential         Not available         Not available	2 2 		
	Vaphtha (petrole tydrocarbons C vixture CIT EC 2 viture CIT EC 2 vote: Biodegrad BIOACCUMULAT vot available. Bioaccumulation or individual ing vaphtha (petrole tydrocarbons C vixture CIT EC 2 VI available. Mobility or individual ing vaphtha (petrole tydrocarbons C vixture CIT EC 2 RESULTS OF PBT	eum), hydrodesulfurized heavy 19-C12 (aromatics 2-25%) 247-500-7 MIT EC 220-239-6 (3:1) lability data correspond to an average of da TIVE POTENTIAL: 1 1 1 1 1 1 1 1 1 1 1 1 1	of Regulation (EC) no	log Pow 5.65 5.65 -0.830 log Koc 4.90 4.90 -1.22	L/kg       > 100.       (calculated)       3.2       (calculated)       Constant of Henry	Potential         Not available         Not available         Not available         Potential         Not available         Not available	2 2 		

Date of compilation: 21/11/2019

Page 9/10

n accord	ance with Regulation (EC) No. 1907/2006 and Regulation (EU) No. 2015/880
	NEUCE Microneuce SV 100 - Stucco Veneziano Code: 12640000
12.6	OTHER AD VERSE EFFECTS: Ozone depletion potential: Not available. Photochemical ozone creation potential: Not available. Earth global warming potential: Not available. Endocrine disrupting potential: Not available.
SECTI	ION 13 : DISPOSAL CONSIDERATIONS
13.1	WASTE TREATMENT METHODS: Directive 2008/98/EC~Regulation (EU) no. 1357/2014: Take all necessary measures to prevent the production of waste whenever possible. Analyse possible methods for revaluation or recycling. Do not discharge into drains or the environment, dispose at an authorised waste collection point. Wast e should be handled and disposed in a coordance with current local and national regulations. For exposure controls and personal protection measures, see section 8.
	Disposal of empty containers: Directive 94/62/EC~2015/720/EU, Decision 2000/532/EC~2014/955/EU: Emptied containers and packaging should be disposed in accordance with currently local and national regulations. The classification of packaging as hazardous waste will depend on the degree of empting of the same, being the holder of the residue responsible for their classification, in accordance with Chapter 15 01 of Decision 2000/532/EC, and forwarding to the appropriate final destination. With contaminated containers and packaging, adopt the same measures as for the product in itself.
	Procedures for neutralising or destroying the product: Authorised landfill in accordance with local regulations.
SECTI	ION 14 : TRANSPORT INFORMATION
14.1	UN NUMBER: Not applicable
14.2	UN PROPER SHIPPING NAME: Not applicable
14.3	TRANSPORT HAZARD CLASS(ES): Transport by road (ADR 2019) and Transport by rail (RID 2019):
	In al Sport by Fail (ND 2019).       Not regulated <u>Transport by sea (IMDG 38-16):</u> Not regulated
	Transport by air (ICAO/IATA 2018): Not regulated
	Transport by inland waterways (ADN): Not regulated
14.4	PACKING GROUP: Not regulated
14.5	ENVIRONMENTAL HAZARDS: Not applicable (not classified as hazardous for the environment).
14.6	SPECIAL PRECAUTIONS FOR USER: Ensure that persons transporting the product know what to do in case of accident or spill. Always transport in closed containers that are upright and secure.
14.7	TRANSPORT IN BULK ACCORDING TO ANNEXIIOF MARPOL 73/78 AND THE IBC COD E. Not applicable.
SECTI	ION 15 : REGULATORY INFORMATION
15.1	EU SAFETY, HEALT HAND ENVIRONMENTAL REGULATIONS/LEGISLATION SPECIFIC: The regulations applicable to this product generally are listed throughout this Safety Data Sheet.
	Restrictions on manufacture, placing on market and use: See section 1.2
	Tactile warning of danger: Not applicable (the classification criteria are not met).
	Child safety protection: Not applicable (the classification criteria are not met).
	VOC information on the label: Contains VOC max. 19. g/l - The limit value 2004/42/CE-IIA cat. k) for the product ready for use is VOC max. 100. g/l (2010).
	OTHER REGULATIONS:
	Control of the risks inherent in major accidents (Seveso III): See section 7.2
	Other local legislations: The receiver should verify the possible existence of local regulations applicable to the chemical.
15.2	CHEMICAL SAFETY ASSESSMENT:         A chemical safety assessment has not been carried out for this mixture.

The information of this Safety Data Sheet, is based on the present state of knowledge and on current UE and national laws, as the users' working conditions are beyond our knowledge and control. The product is not to be used for other purposes than those specified, without first obtaining written handling instruction. It is always the responsibility of the user to take all necessary steps in order to fulfil the demand laid down in the local rules and legislation. The information in this Safety Data Sheet is meant as a description of the safety requirements of the product and it is not to be considered as a guarantee of the product's properties.