

18.02 – GLUE FOR PARQUET TILES

DESCRIPTION: Formulated with an emulsion of PVA, the “GLUE FOR PARQUET TILES” is indicated for the unilateral gluing of pavements in wood and floors in concrete. It is very used in the Industry of Civil Construction.

FEATURES:

- Easy to apply
- Good adhesion to concrete floors

SPECIFICATIONS:

- **Density**.....1,30 ± 0,10
- **Viscosity**..... 35000/38000 cP
(Brookfield RVT sp6 20 rpm)
- **Color**..... dark and light brown
- **Time to glue**.....Approx. 15 minutes*
- **Working temperature**.....Approx. 20°C (recommended)
- **Tenor of solids**.....66.5%.

*Depending on the room temperature and humidity conditions, as well as on the soil porosity and the quantity of the glue applied.

SURFACE PREPARATION: The surfaces to glue have to be levelled and alike, as well as free of dust, oils and grease. The flooring humidity degree can't be superior to 2.5%.

APPLICATION: Before to use mix energetically the product.
The application obeys to the following steps:

1. To apply a layer of glue in the flooring, with a “notched trowel” with the following features:
Notches depth: 3 mm
Notched width : 4 mm
Space between notches: 3 mm
2. To apply the wood strips, parquet and flooring (stable with a moisture content of 10 to 12%) over the glue, pushing on the whole area to glue, so that the gluing process is evenly realized.
3. Let it dry at least during 48 hours so to be realized the lowering or polishing of the wood. The newly glued floor should not be wet.

DILUTION: This product is supplied ready to use.

COVERAGE: Variable according to the glue layer.
As an orientation: 1 – 1,25 m²/kg of the product.

CLEAN-UP: With water, right after the application.

WARNING:

This product is not irritant nor presents any risks of sensitization in a contact with skin. In spite of presenting no risks for health, it is advised to keep out of reach of children. For further information, the reading of our product **Safety Data Sheet** is essential.

RECOMMENDATIONS:

Do not apply the product with a cold or humid weather. These factors influence the drying and the glue performance.

It is essential to “comb” the glue with a “notched trowel” before to apply on the wood pavement, since the channels that result from it are what helps to get a good leveling and efficient glue drying.

**STORAGE
AND
PACKAGING:**

The containers should be kept properly closed, and the product spent by chronological order of supply, in a maximum period of 12 months.

It is supplied in packages of 7,0 and 20 kg.