

## 01.06 – PLIONEUCE SEALER – Anti-Saltpeter

**DESCRIPTION:**



Based on a combination of acrylic resins of solvent basis, this product was developed to allow an optimal “sealing” of too alkaline plasters and also to allow an efficient fight against saltpeter development. Helps in the consolidation, fixation of surfaces thanks to its efficient penetration on them.

**FEATURES:**

- Great resistance to chemical agents.
- Resistant to alkalinity.
- Resistant to fungus development.
- It combats efficiently saltpeter.

**SPECIFICATIONS:**

- **Density**.....0,820 ± 0,05
- **Viscosity**..... 15 ± 2” Ford IV (20°C)
- **Color**.....Transparent, colorless
- **Superficial drying** .....4 to 6 hours
- **Depth drying**.....± 24 hours
- **VOC (volatile organic compound)**....<sup>a)</sup> EU limit value set for this product cat. (A/h) 750 g/l (2010). This product contains a maximum of 722 g/l VOC.

**RECOMMENDED USE:**

It is used as sealer of interior and exterior plaster walls, especially when these have obvious presence of efflorescence or saltpeter. It can still be applied over stone or concrete. It is an excellent basis for any type of “water based paint” and even for paint based on “PLIONEUCE”.

**SURFACE PREPARATION:**

Surfaces have to be clean, dry, free of dust, dirt, and mosses. Concerning repainting, a good brushing of the wall is advised, in order to eliminate badly-adhered paint remains.

**APPLICATION:**

Before to use mix energetically the product. The application is to be realized with a roller or a paint-brush, in a single coat without dilution.

**DILUTION:**

This product is supplied ready to use.

**COVERAGE:**

Variable according to the surface absorption. On average and per coat: 8 to 10 m<sup>2</sup>/liter.

**CLEAN-UP:** With “PLIOLITE DILUENT” or “CELLULOSE DILUENT” right after the application.

**WARNING:**

- Although it is not a product with a very active smell, the local shall have a good air renewal.
- In case of contact with the skin or the eyes to wash with plenty of water.

**STORAGE AND PACKAGING:** Packages should be kept properly closed, in good environmental conditions of temperature and humidity, and spend the product on the chronological order of supply.  
Use it, with preference, up to 2 years after its manufactured date, but it can also be used after this date, as long as a good homogenization of the product can be verified.  
It is supplied in packages of 1lt, 5lt and 15 liters.

Note a) The value of the VOC previously mentioned concerns ready-to-use products, according to the technical specifications that we recommend. We do not take any responsibility for other mixtures made to the product. We draw special attention to all our agents for the responsibility that they take by not respecting what the Directive 2004/42/CE establishes