

01.07 – PLIONEUCE PRIMER – Anti-Saltpeter Primer

DESCRIPTION:



Prepared with a combination of acrylic resins of solvent basis, this primer has a good penetration action in the substrates, making it stable and improving the adhesion of finish paints. Fights efficiently saltpeter development.

Is indicated as a basis for "PLIONEUCE" on facades painting.

FEATURES:

- Fix, seal and agglutinate substrates.
- Excellent resistance to alkalinity.
- Excellent adhesion.
- Impermeable to water but permeable to water vapor.
- Resistant to fungus development.

SPECIFICATIONS:	 Density
RECOMMENDED USE:	It is used as primer for "PLIONEUCE" in the painting of facades. It can still be used as "insulation" in interior walls, when these present problems such as alkalinity, and when the intention is to minimize even eliminate them. It is an excellent basis for any type of "water based paint".
SURFACE PREPARATION:	Facades have to be clean, dry, free of dust, grease, dirt, and mosses. Concerning repainting, a good brushing of the surface is advised, in order to eliminate badly-adhered paint remains.
APPLICATION:	Before to use mix energetically the product. The application is to be realized with a roller or a paint-brush, in a single coat without dilution.
DILUTION:	This product is supplied ready to use. It admits a dilution with "PLIONEUCE DILUENT", for special situations.



COVERAGE:	Variable according to the surface absorption. On average and per coat: 7 to 9 m ² /liter.
CLEAN-UP:	With "PLIONEUCE DILUENT", right after the application.
WARNING:	 Although it is not a product with a very active smell, the local shall have a good air renewal. When applied with a spray-gun to use a mask and protection gloves. In case of a contact with the skin or the eyes to wash with plenty of water. To keep out of reach of children. For further information, the reading of our product <u>Safety Data Sheet</u> is essential
STORAGE AND PACKAGING:	Packages should be kept properly closed, in good environmental conditions of temperature and humidity, and spend the product on the chronological order of supply. Use it, with preference, up to 2 years after its manufactured date, but it can also be used after this date, as long as a good homogenization of the product can be verified. It is supplied in packages of 11t, 51t and 15 liters.

Note a) The value of the VOC previously mentioned concerns ready-to-use products, according to the technical specifications that we recommend. We do not take any responsibility for other mixtures made to the product. We draw special attention to all our agents for the responsibility that they take by not respecting what the Directive 2004/42/CE establishes