

## 13.01 – OILY PUTTY FOR WOOD

- DESCRIPTION:** Based on a balanced mixture of long alkyd resins in oil and natural oils, “OILY PUTTY FOR WOOD”, is appropriated for the leveling and filling of irregularities in the wood.
- FEATURES:**
- Great adhesion.
  - Good filling and easy to sand.
  - Good hardness after dry.
- SPECIFICATIONS:**
- **Density**.....1,820 ± 0,10
  - **Viscosity**.....280 ± 25 Poises.(25°C)
  - **Color**.....Yellowish white.
  - **Aspect**.....Pasty
  - **Superficial drying**.....4 to 6 hours.
  - **Depth drying**.....±24 hours
  - **Sanding**.....At the end of 24 hours.
  - **VOC (volatile organic compound)**....<sup>a)</sup> EU limit value set for this product cat. (A/g) 350 g/l (2010). This product contains a maximum of 220 g/l VOC.
- RECOMMENDED USE:** “OILY PUTTY FOR WOOD”, is appropriated for the leveling and filling of wood irregularities and holes. That’s the reason why, it is used in civil construction in the “filling” of doors, windows, panels. After well dried and sanded, this putty provides a great surface for the application of “NEUCECAPA- Synthetic Universal Undercoat” and enamel of synthetic root as a finish.
- SURFACE PREPARATION:** Wood surfaces have to be clean, dry and properly sanded.
- APPLICATION:** To homogenize well the product before to apply, so that the paste remains malleable.  
It is applied with a putty-knife, without dilution, in the wanted thickness.
- DILUTION:** With “SYNTHETIC DILUENT”, when necessary.
- COVERAGE:** Variable, depending on the thickness layer.



- CLEAN-UP:** With “SYNTHETIC DILUENT”, right after the application.
- WARNING:** In the case of a contact with the skin or the eyes, to wash with plenty of water.
- RECOMMENDATIONS:** Do not apply in cold or humid days, nor on “green” wood.
- STORAGE AND PACKAGING:** Packages should be kept properly closed, in good environmental conditions of temperature and humidity, and spend the product on the chronological order of supply.  
Use it, with preference, up to 1 years after its manufactured date, but it can also be used after this date, as long as a good homogenization of the product can be verified.  
It is supplied in packages of 1 and 5 Kg.

Note a) The value of the VOC previously mentioned concerns ready-to-use products, according to the technical specifications that we recommend. We do not take any responsibility for other mixtures made to the product. We draw special attention to all our agents for the responsibility that they take by not respecting what the Directive 2004/42/CE establishes.