

## 43.04 - ACRYLIC DILUENT and RETARDANT ACRYLIC DILUENT

USE:	This thinner is used in the dilution of all of the products of acrylic root, namely:
	<ul> <li>"NEUCETELHA"</li> <li>"PURNEUCE"</li> <li>"SOLNEUCE"</li> <li>"NEUCEROAD"</li> <li>"NEUCEROAD REFLEX"</li> <li>"ACRYLIC VARNISH FOR METALS"</li> </ul>
	When a slower drying of these products is pretended (paint-brush applications), it is used in the dilution, instead of the "ACRYLIC DILUENT", the "RETARDANT ACRYLIC DILUENT" which make possible a more extended "opened time" allowing a better application.
COMPOSITION:	<ul><li>- Aromatic solvents.</li><li>- Propylene glycol methyl ether.</li></ul>
SPECIFICATIONS:	- <b>Density</b> 0,900±0,05
	<ul> <li>ColorColorless</li> <li>AspectLiquid, transparent.</li> <li>Flashpoint17 a 25°C</li> </ul>
HANDLING:	<ul> <li>ColorColorless</li> <li>AspectLiquid, transparent.</li> </ul>

Neuce s.a., the right is reserved of altering any constant data in this publication without notice  $Edition\ n.^{o}\ 5\ \ 2021-05-10$