

44.01 – EURONEUCE – White Acrylic Paint

DESCRIPTION:



Based on a styrene acrylic emulsion, this paint has been especially developed for interior painting with a good covering, being also recommended for exterior painting. Provides a good resistance to alkalinity.

FEATURES:

- Easy to use.
- Good adhesion and coverage.
- Good covering and whiteness.
- Reasonable resistance to washing.

SPECIFICATIONS:

- **Density** 1,600 ± 0,10
- **Viscosity**..... 85-115Ku (25°C)
- **Color**..... White
- **Finishing**..... Matte
- **% Solids in volume**..... 40±5%
- **Dry-to-touch**..... ± 1 hour
- **Depth drying**..... ± 24 hours
- **Flashpoint** non-flammable
- **VOC (volatile organic composites)** ^{a)} EU limit value for this product cat. (A/a) 30 g/l (2010). This product contains 9 g/l VOC maximum.

RECOMMENDED USE: Destined to walls painting of flat and sand-finish plaster in the interior and exterior, offering a matte finish with a good covering.

SURFACE PREPARATION:

The new plaster has to be clean, dry, hard, free of dirt or dust. Concerning repainting to brush properly the wall in order to eliminate any old painting remains or to exfoliate.

SURFACE INSULATION:

A careful choice of the 1st coat (insulation) helps to obtain a better finish and to solve certain existing problems in the painting surface.

We recommend as special insulations:

- One coat of “PLIONEUCE PRIMER” – No dilution.
- One coat of “AQUANEUCE - WHITE WATER BASED PRIMER” – No dilution.
- One coat of “MARSOL – High Filling Acrylic Primer” – Diluted at 10% with water.

- APPLICATION:** Before to use mix energetically the product.
The application is made with a paint-brush, a roller or a spray-gun in 2 to 3 coats properly diluted and spaced out from 12 to 24 hours.
- DILUTION:** With water in the approximate following proportions:
1st Coat.....10%
Others.....5% to 10%
- COVERAGE:** Variable according to the support's absorption, and the application conditions.
On average and per coat 8 to 10 m² / liter.
- CLEAN-UP:** With water right after the application.
- WARNING:** A selection of this product components has a tenor in clorometilisotiazolinona/metilisotiazolinona 3:1 inferior to 15 ppm, according to the Community Directive n°98/8/EC indications. Hence this product is not irritant nor presents any risks of sensitization in a contact with skin.
In spite of presenting no risks for health, it is advised to keep out of reach of children.
- RECOMMENDATIONS:** It is important to use this product with good weather conditions, that is to say, do not use in rainy or very cold days.
- STORAGE AND PACKAGING:** Packages should be kept properly closed, in good environmental conditions of temperature and humidity, and spend the product on the chronological order of supply.
Use it, with preference, up to 2 years after its manufactured date, but it can also be used after this date, as long as a good homogenization of the product can be verified.
It is supplied in packages of 5lt and 15 liters.

Note a) The value of the VOC previously mentioned concerns ready-to-use products, according to the technical specifications that we recommend. We do not take any responsibility for other mixtures made to the product. We draw special attention to all our agents for the responsibility that they take by not respecting what the Directive 2004/42/CE establishes.