

## F1 – CARAPAS MASS – Interiors Coating

### DESCRIPTION:



This mass is based on a mixture of water-based dispersions, with pigments and selected charges, which provides to it all the filling features, elasticity and hardness of a good acrylic mass.

### FEATURES:

- Easy to apply and good adhesion.
- Good filling and great malleability.
- Good coverage and whiteness.
- Good hardness.

### SPECIFICATIONS:

- **Density**.....1,600 ± 0,10
- **Viscosity**..... 210 ± 25 Poises (25°C)
- **Color**.....White
- **Aspect**.....Pasty
- **Finishing**.....”Tear-like” characteristic
- **Dry-to-touch**.....6 to 12 hours
- **Depth drying**.....24 to 48 hours
- **Paint**.....After dry
- **Tenor in CIT/MIT**.....<15 ppm
- **VOC (volatile organic compound)**...<sup>a)</sup> EU limit value set for this product cat. (A/g) 30 g/l (2010). This product contains a maximum of 26 g/l VOC.

### RECOMMENDED USE:

It is essentially recommended for the paneling’ coating, when the intention is to transmit to this wall area a finish with its own relief, and simultaneously to correct certain imperfections. After dry and hard, “CARAPAS MASS” is also a great support for the most diverse enamels of finish, from the chemical-resistant, enamels of epoxy root with a solvent base or a water based base, or a chlorinated rubber, to the traditional, enamel of water based acrylic root.

### SURFACE PREPARATION:

Walls have to be properly clean, dry, hard and free of badly adhered sands.

### SURFACE INSULATION:

Before the application of “CARAPAS MASS”, we recommended as special insulators:

- One coat of “PLIONEUCE PRIMER” – No dilution.
- One coat of “HYDRONEUCE PRIMER” – No dilution.

- APPLICATION:** Before to use homogenize well the product.  
The product is to be applied in a single coat. It is spread with a brush adapted to small areas, in a homogenize way, and then, threw the use of a proper rubber roller that provides a textured aspect (relief).  
The last roller application should be made from the bottom to the top.  
Slightly diluted “CARAPAS MASS” provides a more rounded and flat texture.
- DILUTION:** With water, if necessary.
- COVERAGE:** In average 1 Kg/m<sup>2</sup>.
- CLEAN-UP:** With water right after the application.
- WARNING:** This product is not irritant nor presents any risks of sensitization in a contact with skin. In spite of presenting no risks for health, it is advised to keep out of reach of children. For further information, the reading of our product **Safety Data Sheet** is essential
- RECOMMENDATIONS:** The application should be avoided with a cold or rainy weather because the drying is slower.  
Do not apply the finish enamel without “CARAPAS MASS” being very dry. It can cause posterior “peelings”.
- STORAGE AND PACKAGING:** Packages should be kept properly closed, in good environmental conditions of temperature and humidity, and spend the product on the chronological order of supply.  
Use it, with preference, up to 2 years after its manufactured date, but it can also be used after this date, as long as a good homogenization of the product can be verified.  
It is supplied in packages of 7,5 and 25 Kg.

Note a) The value of the VOC previously mentioned concerns ready-to-use products, according to the technical specifications that we recommend. We do not take any responsibility for other mixtures made to the product. We draw special attention to all our agents for the responsibility that they take by not respecting what the Directive 2004/42/CE establishes.