

## F4 – NEUCEGRANI – Decorative Wall Coating

**DESCRIPTION:**



Decorative coating for interior and exterior finishes, based on synthetic polymers in water based emulsion, with colored grains, chemically inert, calibrated and selected.  
Presents great resistance to abrasion, impact and climatic contrasts.  
Provides a beautiful imitation of natural stone.

**FEATURES:**

- Great adhesion on plaster and concrete.
- Good water impermeability.
- High permeability to water vapor.
- High resistance to bad weather.
- Hides the surface imperfections.
- Nice decorative effect.
- Washable.

**SPECIFICATIONS:**

- **Density**.....1,690 ± 0,10
- **Color**.....As in the catalog
- **Consistency**.....Pasty
- **Finishing**.....Sand-finish
- **Drying**.....8 to 48 hours, according to the room temperature and humidity during the application
- **VOC (volatile organic compound)**....<sup>a)</sup> EU limit value set for this product cat. (A/1) 200 g/l (2010). This product contains a maximum of 28 g/l VOC.

**RECOMMENDED USE:**

"NEUCEGRANI" is destined to substrates protection and decoration, such as concrete, mortar, traditional plaster, etc., in interior and exterior civil construction, such as paneling, columns frames of doors and windows, walls of stairway enclosures, facades, etc.

**SURFACE PREPARATION:**

The coating surfaces have to be clean, dry, degreased, free of dust, free sands and dirt, slightly rough and well fixed, with the capacity to support the load of the finish product.  
Walls contaminated with fungi, algae, mosses, etc., have to be washed / scrubbed with bleach, wash very well with running water, let dry and then apply a thick coat of "DISINFECTANT SOLUTION".  
Concerning dusty or friable surfaces, or when there is a need to regularize the surface and repair micro-cracks, to apply "IMPERNEUCE" mixed in equal parts with cement.

To let dry 24 to 48 hours.

To homogenize the surface color, to apply 1 coat of "NEUCEGRANI PRIMER".

- APPLICATION:** Before to start the application, to mix well the product, **without using any mechanical mean**, to obtain its good homogenization. "NEUCEGRANI" is applied with a trowel in a single coat, according to the proper technique. To spread with a stainless steel trowel a layer of the product, pressing and pulling from the bottom to the top, to obtain a constant thickness, equal to the grains size. After a few minutes, to use the stainless steel trowel again, exercising some pressure on it, in the horizontal and vertical way, until obtaining a homogenize layer. The trowel should be washed regularly with water so that it slides easily on the coating. To be applied only by professionals.
- DILUTION:** "NEUCEGRANI" is supplied ready to use.
- COVERAGE:** Variable according to the type of support used, the application and the final aspect that is pretended. On average 4 to 5 kg / m<sup>2</sup>.
- CLEAN-UP:** With water right after the application.
- WARNING:** A selection of this product components has a tenor in clorometilisotiazolinona/metilisotiazolinona 3:1 inferior to 15 ppm, according to the Community Directive n°98/8/EC indications. Hence this product is not irritant nor presents any risks of sensitization in a contact with skin. To keep out of reach of children. For further information, the reading of our product **Safety Data Sheet** is essential.
- RECOMMENDATIONS:**
- Do not apply the product with a room temperature inferior to 10 ° C nor superior to 35 ° C or in adverse weather conditions, rain or much wind.
  - When using the adhesive tape to protect areas not to coat, this should be removed when the product is still humid.
  - When realizing the work, to use the product in the same manufactured order (MO), because there may exist differences of color shades between different MO. To check the color before the application.

**STORAGE  
AND  
PACKAGING:**

Packages should be kept properly closed, in good environmental conditions of temperature and humidity, and spend the product on the chronological order of supply.

Use it, with preference, up to 1 year after its manufactured date.

It is supplied in packages of 25 Kg.

Note a) The value of the VOC previously mentioned concerns ready-to-use products, according to the technical specifications that we recommend. We do not take any responsibility for other mixtures made to the product. We draw special attention to all our agents for the responsibility that they take by not respecting what the Directive 2004/42/CE establishes.