

G2 – COUVERTEK NORMAL

DESCRIPTION:



White water based mass of sand-finish texture, ready to apply, with a filling and homogenization power for interior surfaces, in particular walls and ceilings, in the most diverse types of substrates allowing to obtain a surface with good conditions to proceed to the final decoration

FEATURES:

- Easy to apply.
- Good adhesion.
- Easy to sand.
- Good resistance.
- Great permeability to water vapor.
- Good filling.

SPECIFICATIONS:

- **Density**.....1710 ± 0,10
- **Viscosity**..... 650 ± 50 Poises (25°C)
- **Color**.....White
- **Aspect**.....Pasty
- **Dry-to-touch**.....± 1 hour
- **Depth drying**.....± 24 hours, variable on the filling thickness
- **Tenor in CIT/MIT**.....<15 ppm
- **VOC (volatile organic compound)**....^{a)} EU limit value set for this product cat. (A/1) 200 g/l (2010). This product contains a maximum of 26 g/l VOC.

RECOMMENDED USE:

“COUVERTEK NORMAL” is a product used for stucco work of walls and interior ceilings, on a large variety of materials, such as, brick, concrete blocks, fiber-cement, cement plaster, etc, has an excellent performance in the filling of small holes, cracks and undulations, allowing the leveling of surfaces.

SURFACE PREPARATION:

Existing holes, cracks, etc. must be properly cleaned in order to free any dusts or badly adhered materials. Holes bigger than 5 mm have to be previously filled by layers. Surfaces have to be dry.

- APPLICATION:** Before to use mix the product.
To apply manually or mechanically by projection using the proper equipment, the homogenization of the layer is always made manually with an appropriate putty knife, leaving the surface flat withdrawing the excess of product that can be reused.
With the second layer application, which may remain with some decorative effects (for example: textured effect) or not.
The application between layers has to be made with, more or less, 1 hour of interval.
After dried, the surface can be sanded, using a fine sandpaper. Before the final finishing all the caused dust has to be eliminated.
At the end of 24 hours, the whole surface has to be painted with the appropriate paint.
- DILUTION:** This product is supplied ready to use.
- COVERAGE:** Variable according to the layer thickness and the surface porosity. As an orientation, we can indicate 1,5 kg/m² per coat.
- CLEAN-UP:** With water right after the application.
- WARNING:** A selection of this product components has a tenor in clorometilisotiazolinona/metilisotiazolinona 3:1 inferior to 15 ppm, according to the Community Directive n°98/8/EC indications. Hence this product is not irritant nor presents any risks of sensitization in a contact with skin.
In spite of presenting no risks for health, to keep out of reach of children.
- STORAGE AND PACKAGING:** Packages should be kept properly closed, in good environmental conditions of temperature and humidity, and spend the product on the chronological order of supply.
Use it, with preference, up to 1 year after its manufactured date, but it can also be used after this date, as long as a good homogenization of the product can be verified.
It is supplied in packages of 25kg.

Note a) The value of the VOC previously mentioned concerns ready-to-use products, according to the technical specifications that we recommend. We do not take any responsibility for other mixtures made to the product. We draw special attention to all our agents for the responsibility that they take by not respecting what the Directive 2004/42/CE establishes