

## I1 – NEUCETELHA WB – Water-based Paint for Tiles

**DESCRIPTION:**

This 100% pure acrylic paint of good quality and is appropriated for the painting of tiles or fiber-cement plates.



**FEATURES:**

- Easy to apply and good adhesion.
- Good covering and resistance to bad weather.
- Excellent color retention.

**SPECIFICATIONS:**

- **Density**.....1,400 ± 0,10
- **Viscosity**.....85-115 ku (20°C)
- **Color**.....Catalog colors of tiles paints
- **Dry-to-touch**.....2 to 4 hours.
- **Depth drying** .....± 24 hours
- **Tenor in CIT/MIT**.....< 15 ppm
- **VOC (volatile organic composites)** .....<sup>a)</sup> EU limit value for this product cat. (A/i) 140 g/l (2010). This product contains 19 g/l VOC maximum.

**RECOMMENDED USE:**

This product is appropriated for applications on tile or fiber-cement plates. Thanks to its composition it can also be applied on concrete or even on sand-finish plaster.

**SURFACE PREPARATION:**

Both the tiles and the fiber-cement plates have to be dry, free of dirt or mosses. On used roofs, it is usual to effectuate a cleaning with a pressurized water-jet cleaning gun for a “complete cleaning”. On new roofs a good brushing is enough.

**APPLICATION:**

Before to use homogenize well the product.  
The application is to be realized with a paint-brush or a roller, in 2 to 3 coats properly diluted and spaced out from 2 to 4 hours.  
For a good penetration the 1<sup>st</sup> coat has to be diluted between 20 to 25% with water, while the remaining ones (of finish) should only be diluted up to 10%.

**DILUTION:**

With water.

**COVERAGE:**

On average and per coat: 7 to 9 m<sup>2</sup>/liter.

**CLEAN-UP:** With water right after the application.

**WARNING:** A selection of this product components has a tenor in clorometilisotiazolinona/metilisotiazolinona 3:1 inferior to 15 ppm, according to the Community Directive n°98/8/EC indications. Hence this product is not irritant nor presents any risks of sensitization in a contact with skin.

In spite of presenting no risks for health, it is advised to keep out of reach of children.

**RECOMMENDATIONS:** Do not apply the product by a rainy or cold weather. On the other hand, in the summer, to avoid the application in the hottest hours. The quick drying is unfavorable to a good penetration. Do not apply the product at the first hours of the morning. The “nocturne fog” maintains the tiles humidity, which can originate posterior “peelings”.

**STORAGE  
AND  
PACKAGING:**

Packages should be kept properly closed, in good environmental conditions of temperature and humidity, and spend the product on the chronological order of supply.

Use it, with preference, up to 2 years after its manufactured date, but it can also be used after this date, as long as a good homogenization of the product can be verified.

It is supplied in packages of 1lt, 5lt and 15 liters.

Note a) The value of the VOC previously mentioned concerns ready-to-use products, according to the technical specifications that we recommend. We do not take any responsibility for other mixtures made to the product. We draw special attention to all our agents for the responsibility that they take by not respecting what the Directive 2004/42/CE establishes.