

## I2 – NEUCETELHA – Solvent Based Acrylic Paint for Tiles

### DESCRIPTION:



Paint formulated with special resins of solvent base, appropriated for applications on porous tile or fiber-cement plates, and it can also be applied on concrete or sand-finish plaster.

### FEATURES:

- Easy to apply and good adhesion.
- Good covering.
- Resistant to bad weather.
- Good impermeability of the tile.

### SPECIFICATIONS:

- **Density**.....1,317 ± 0,10
- **Viscosity**.....150 ± 23” Ford IV (20°C)
- **Color**.....Black and others
- **Finishing**.....Matte
- **Superficial drying**.....± 30 minutes
- **Depth drying**.....± 2 to 4 hores
- **VOC (volatile organic composites)** .....<sup>a)</sup> EU limit value set for this product cat. (A/i) 500 g/l (2010). This product contains a maximum of 500 g/l VOC.

### RECOMMENDED USE:

This paint is especially recommended for the painting of tiles and new fiber-cement plates.  
Concerning used tiles or fiber-cement plates, it is necessary to guarantee a complete cleaning before the application.

### SURFACE PREPARATION:

The surface has to be clean, dry, free of dirt and mosses.  
On porous tiles or new fiber-cement, to remove dusts through an efficient brushing is enough.  
On porous tile or used fiber-cement, to effectuate a cleaning with a pressurized water-jet cleaning gun is necessary.  
This paint good performance and adhesion also depend on the efficient cleaning of the surface.

**SURFACE  
INSULATION:**

We recommended as insulation (1st coat):

- A coat of the own paint diluted with “ACRYLIC DILUENT” up to 20%.

To pay attention that the presence of humidity can cause “peelings”.

**APPLICATION:**

Before to use mix energetically the product.

The application is to be realized with a paint-brush or roller (preferentially), or with a spray-gun, with 2 to 3 coats properly diluted and spaced out from 6 to 12 hours.

**DILUTION:**

It is done with “ACRYLIC DILUENT” in the following percentages:

Roller or Paint-brush:

1<sup>st</sup> coat.....10%  
Others.....5 to 10%

Spray-gun: 10 to 15% in all of the coats, having the paint sprayed at a low pressure.

**COVERAGE:**

Variable according to the support’s absorption, and the application conditions.

On average and per coat 7 to 9 m<sup>2</sup> / liter.

**CLEAN-UP:**

With “CELLULOSE DILUENT”, right after the application.

**WARNING:**

- To apply in places with a good air renewal.
- To use protection mask and gloves when applied with a spray-gun.
- Inflammable product.
- In the case of a contact with the skin or the eyes, to wash with plenty of water.
- Toxic by inhalation or ingestion. In case of ingestion to call for a doctor.

**STORAGE AND  
PACKAGING:**

Packages should be kept properly closed, in good environmental conditions of temperature and humidity, and spend the product on the chronological order of supply.

Use it, with preference, up to 2 years after its manufactured date, but it can also be used after this date, as long as a good homogenization of the product can be verified.

It is supplied in packages of 1lt, 5lt and 20 liters.

Note a) The value of the VOC previously mentioned concerns ready-to-use products, according to the technical specifications that we recommend. We do not take any responsibility for other mixtures made to the product. We draw special attention to all our agents for the responsibility that they take by not respecting what the Directive 2004/42/CE establishes.