

## P4 – ALUNEUCE NT 300 Cellulose Aluminium

**DESCRIPTION:** It is a product of nitro-synthetic nature, pigmented with aluminium of fine grain “leafing type”, characterized by the association of a glossy metallic finish with a very quick drying. It can also be used both in the interior and in the exterior. <sup>a)</sup>

**FEATURES:**

- Easy to apply and good covering.
- Very quick drying.
- Good flexibility
- Good resistance to bad weather

**SPECIFICATIONS:**

- **Density**.....0,960 ± 0,05
- **Viscosity**.....59-81 ku (20°C)
- **Color**..... Grey, aluminium-like.
- **Finishing**.....Glossy.
- **Superficial drying**.....± 10 minutes.
- **Depth drying**.....1 to 2 hours.
- **VOC** ..... <669 g/l
- **VOC (Cellulose Dil.)** ..... <850 g/l

**RECOMMENDED USE:** **ALUNEUCE NT 300** is very used as a finish product over metallic surfaces, which should already be properly protected with a resistant primer such as **NEUCERAPID PRIMER**. Therefore, thanks to its resistance, flexibility, gloss and quick drying, it is common to realize finishes with **ALUNEUCE NT 300** in the metal-mechanical industry, in the ornamentation painting of bicycle panels and other similar pieces.

**SURFACE PREPARATION:** Very often, the pellicular defects of the paints are the consequence of a deficient surface preparation. Therefore, to make sure that the metallic surface is dry, clean, free of oxides, degreased and already properly protected with a resistant primer such as **NEUCERAPID PRIMER**.

**APPLICATION:** To homogenize well the product before to use. It is applied with a conventional spray-gun (preferentially), in a single coat, properly diluted, but in a sufficient layer that ensures a dry film thickness of ±25 µm. It can also be applied with a paint-brush.

- DILUTION:** With “CELLULOSE DILUENT” in the following approximate proportions:
- Spray-gun.....10 to 15% (Viscosity ± 25" Ford IV).  
Paint-brush.....5 to 10% (Viscosity ± 60" Ford IV).
- COVERAGE:** On average: 8 to 10 m<sup>2</sup>/liter.
- CLEAN-UP:** With "CELLULOSE DILUENT", right after the application.
- WARNING:**
- Inflammable product.
  - In the case of a contact with the skin or the eyes, to wash with plenty of water.
  - Toxic by inhalation or ingestion.
  - For further information, please read our product **Safety Data Sheet**.
- RECOMMENDATIONS:** Do not apply with temperatures inferior to 5°C or with a rainy weather.
- STORAGE AND PACKAGING:** Packages should be kept properly closed, in good environmental conditions of temperature and humidity, and spend the product on the chronological order of supply.  
Use it, with preference, up to 2 years after its manufactured date, but it can also be used after this date, as long as a good homogenization of the product can be verified.  
It is supplied in packages of 1lt and 5 liters.

Note a): According to the Directives 1999/13/EC and 2004/42/EC, this product can be used without limitations in activities performed in a registered or authorized facility.