

## S6 – MARNEUCE – Maritime Varnish

### DESCRIPTION:



This varnish is based on high quality alkyd resins that provide a good resistance to the chlorides and the ultraviolet rays of the solar light, turning it appropriate to the varnishing of wood in the waterfront.

### FEATURES:

- Easy to apply
- Good gloss and good filling
- Resistant to atmospheric agentes
- Long lasting
- Resistant to solar light U.V.

### SPECIFICATIONS:

- **Density**.....0,900 ± 0,05
- **Viscosity**.....85 ± 13” Ford IV (20°C)
- **Color**.....Colorless.
- **Finishing**.....Glossy.
- **Superficial drying**.....± 12 hours.
- **Depth drying**.....24 to 48 hours.
- **Drying Between Coats**.....± 12 hours.
- **VOC (volatile organic compound)**...<sup>a)</sup> EU limit value set for this product cat. (A/e) 400 g/l (2010). This product contains a maximum of 400 g/l VOC.

### RECOMMENDED USE:

“MARNEUCE” can be used for the varnishing of wood surfaces, both in the interior as in the exterior. However, given the particular properties of resistance to chlorides and to solar ultraviolet radiation, it is recommended for the varnishing of wood in the exterior and close to the waterfront, in the most diverse situations in civil constructions (doors, windows, wood fences, porches, etc.). It can also be used as reinforcement varnish, when applied over “WOODNEUCE LASURES” to provide a glossy finish of longer durability.

### SURFACE PREPARATION:

Given that the varnish doesn't hide imperfections, but, on the contrary, enhances them, it is important to pay attention to the surface preparation, the good results of the final finish depends on it. Therefore, the wood surface has to be clean, dry, free of dirt or grease, and properly sanded. Concerning previous varnished woods, to proceed to a sanding with a medium grain sandpaper and to remove any dust and grease before

the varnishing.

- APPLICATION:** Before to use mix energetically the product.  
It is applied with a paint-brush or a roller, in 3 coats, properly diluted and spaced out from 12 to 24 hours.  
A soft sanding between the coats is essential for a good finish.
- DILUTION:** If necessary, with SYNTHETIC DILUENT up to 5%.
- COVERAGE:** On average and per coat 8 to 10 m<sup>2</sup>/liter, depending on the wood porosity.
- CLEAN-UP:** With “SYNTHETIC DILUENT” right after the application but it can also be made with “CELLULOSE DILUENT” in the most resistant cases.
- WARNING:**
- Inflammable product.
  - In the case of a contact with the skin or the eyes, to wash with plenty of water.
  - Toxic by inhalation or ingestion.
- RECOMMENDATIONS:** Do not apply the product with temperatures inferior to 5 °C nor with a high room humidity.
- STORAGE AND PACKAGING:** Packages should be kept properly closed, in good environmental conditions of temperature and humidity, and spend the product on the chronological order of supply.  
Use it, with preference, up to 2 years after its manufactured date, but it can also be used after this date, as long as a good homogenization of the product can be verified.  
It is supplied in packages of 0.75lt and 4 liters.

Note a) The value of the VOC previously mentioned concerns ready-to-use products, according to the technical specifications that we recommend. We do not take any responsibility for other mixtures made to the product. We draw special attention to all our agents for the responsibility that they take by not respecting what the Directive 2004/42/CE establishes.