

U50 – MICRONEUCE SV100 - STUCCO VENEZIANO (Mono)
Decorative coating mortar with antique look and a marble effect

DESCRIPTION:



MICRONEUCE SV100 - STUCCO VENEZIANO is a coating highly decorative, smooth, with a natural marble aspect, based on acrylic resins of high quality, charges, pigments and latest generation additives.

It is ideal for the renovation of coating of indoor walls, such as commercial buildings, offices, hotels, showrooms, homes etc., where a heterogeneous and smooth finish is pretended, with a marble decorative effect, like Venetian Plaster.

FEATURES:

“**MICRONEUCE STUCCO VENEZIANO**” is of:

- Easy to apply (One-component)
- Great adhesion capacity to the surface
- Good flexibility
- Great hardness
- Resistant to dirt
- Can be polished with a trowel.

COLOURS:

Available in a large range of colours. **Colours catalogues on demand.**

The colours availability associated to the applicator’s inspiration enables a big diversity of drawings, chromatic aspects and artistic composition.

SPECIFICATIONS:

- **Density**..... 1,5 ± 0,10
- **Viscosity** Pasty
- **Solids content**..... 69%
- **Finishing** Satiny - Glossy
- **Colour**..... Catalogue colours and others (on demand)
- **Waiting time between layers**2 hours (minimum)
- **Final drying** 24 Hours
- **Total hardening**..... after 30 days
- **VOC (volatile organic compound)**...^{a)} EU limit value set for this product cat. (subcat. A/K): 100g/L (2010). This product contains a maximum of 19 g/L de COV.

Note: Results obtained in standard conditions. These times may vary depending on the application temperature (which means, increase with low temperatures and decrease with high temperatures).

RECOMMENDED USE: **MICRONEUCE SV100 - STUCCO VENEZIANO** is versatile and easy to use, this system provides a perfect solution for the decoration of shops, offices, hotels, showrooms, homes, etc, providing a polished finishing, with a marble decorative effect, like Venetian Plaster. It is resistant to dirt and easy to clean.

SURFACE

The surface has to be resistant, stable, smooth, clean and dry.

PREPARATION:

To remove protrusions and over thicknesses, crumbling and little resistant areas. To remove also any type of organic or little absorbent coating.

It shall be uniform and slightly absorbent to be painted (preferably in white or any background colour appropriated to the intended shade) and sanded with a 180 grit sandpaper.

To always check the adhesion degree over stripped surfaces, painted surfaces, façades with ceramic coating, tiles, powder and concrete surfaces. In these cases, we advise to apply 1 coat of **IMPERNEUCE**, mixed with the appropriate proportions with cement and to let dry from 24 to 48 hours.

MORTAR

Ready to use.

PREPARATION:

If the colour tinting will be made with the BIG MIX system, the dye has to be mixed mechanically in the product.

**APPLICATION
METHOD:**

The formation and superficial planimetry of the surface are important for the wished decoration.

After analysing and preparing the surface, to apply **MICRONEUCE SV100 - STUCCO VENEZIANO** according to the classic technique of Venetian Plaster application.

Application Suggestions:

To apply the first layer irregularly with a trowel or stainless-steel spatula, then to fill in the empty spaces in the opposite direction of the previous application. To let dry about 2 horas.

After this time, the surface shall be sanded with a 400 grit sandpaper. To eliminate the existing powder and to apply, with a stainless-steel trowel, thins layers of **MICRONEUCE SV100 - STUCCO VENEZIANO**, irregularly (the size and distance between each can change according to what is pretended). After 2 hours of drying, to fill in the empty spaces in the opposite direction of the previous application. The trowel's size, the number of applications and perhaps the combination of colours, will define the final intended effect.

To let dry for 2 hours and to polish all the surface with a trowel pressing gently to have a superficial gloss and hardness.

To protect the stucco from scratches and dirt, even out the brightness and enhance the color, to sand again the surface with a grit 400 sandpaper and once clean, to apply **NEUCEWAX SV150** with thick and crossed layers.

Once the surface is dry (about 2 hours afterwards), to polish with a cotton cloth. It is very important that before to polish, to confirm that the film is dry and not sticky. To get more gloss and a colour effect, 2 to 3 coats of this wax shall be applied.

COVERAGE: 0,8-1 Kg/m² per coat, depending on the surface conditions and the final result that is pretended.

CLEAN-UP: With water, right after application.

USE

RECOMMENDATIONS: Application temperature: 5°C to 30°C.
Do not apply on surfaces that are friable or little resistant.
This product is easy to clean after 28 days, applying the protection system **NEUCEWAX SV150**.

WARNING: “**MICRONEUCE SV100 - STUCCO VENEZIANO**” doesn’t present any risk for health.
Keep out of the reach of children.
For more information, please read our product **Safety Data Sheet**.

STORAGE

AND

PACKAGING:

Packages should be kept properly closed, in good environmental conditions of temperature and humidity, and spend the product on the chronological order of supply.

Use it, with preference, up to 1 year after its manufactured date.

It is supplied in packages of 5 and 25Kg.

Note a) The value of the VOC previously mentioned concerns ready-to-use products, according to the technical specifications that we recommend. We do not take any responsibility for other mixtures made to the product. We draw special attention to all our agents for the responsibility that they take by not respecting what the Directive 2004/42/CE establishes.