

W5 – NEUCEKOT-FLINTCOUTE

DESCRIPTION: “NEUCEKOT” is a product formulated with the tar, which presents, once dried, and which has great properties of protection. It is recommended to protect immersed and buried structures.

FEATURES:

- Good hardness, resistance and flexibility.
- Good resistance to bad weather.
- Avoids humidity infiltrations.
- Easy to apply and malleability.

SPECIFICATIONS:

- **Density**.....1,580 ± 0,10
- **Viscosity**.....140 ± 25 Poises (20°C)
- **Color**.....Black.
- **Aspect**.....Pasty
- **Superficial drying**.....± 2 hours
- **Depth drying**.....24 to 48 hours
- **VOC (volatile organic compound)**...^{a)} EU limit value set for this product cat. (A/g) 500 g/l (2010). This product contains a maximum of 434 g/l VOC.

**RECOMMENDED
USE:**

This product is recommended for the fence of plasters, on buildings warping, as waterproofer in terraces, in the foundations areas of lands support, etc., avoiding humidity infiltrations. It is also used in the protection of tubes buried to avoid the development of rust, and also in the coating of chassis.

**SURFACE
PREPARATION:**

The plaster surface has to be clean, dry, and free of badly adhered materials.
The iron surface has to be clean, dry, free of rust and properly degreased.

APPLICATION:

Before to use mix energetically the product.
It is applied with a paint-brush or a roller, without dilution or slightly diluted, generally in 3 “thick” coats.
The layer’s thickness determines the bigger or the lower efficiency of the product.

DILUTION:

With "CELLULOSE DILUENT", if necessary, and not exceeding 5%.

- COVERAGE:** Variable, according to the surface absorption and the layer's thickness.
On average and per coat: from 4 to 5 m² / Kg.
- CLEAN-UP:** With "CELLULOSE DILUENT", right after the application.
- WARNING:**
- Inflammable product.
 - To apply in places with a good air renewal.
 - In the case of a contact with the skin or the eyes, to wash with plenty of water.
- STORAGE AND PACKAGING:** Packages should be kept properly closed, in good environmental conditions of temperature and humidity, and spend the product on the chronological order of supply.
Use it, with preference, up to 1 year after its manufactured date, but it can also be used after this date, as long as a good homogenization of the product can be verified.
It is supplied in packages of 5kg and 20 kg.

Note a) The value of the VOC previously mentioned concerns ready-to-use products, according to the technical specifications that we recommend. We do not take any responsibility for other mixtures made to the product. We draw special attention to all our agents for the responsibility that they take by not respecting what the Directive 2004/42/CE establishes.