

39.03 – IMUNEUCE

Wood Protector

DESCRIPTION:	Formulated with a mixture of protective products in an oily environment, this product is destined to the protection and decoration of the wood.
FEATURES:	<ul style="list-style-type: none">- Good wet and penetrating power.- Repel the “wood bug”.
SPECIFICATIONS:	<ul style="list-style-type: none">- Density..... 0,780 ± 0,05- Viscosity..... 15 ± 2" Ford IV (20°C)- Color..... Colorless, Brown and green.- Superficial drying.....±12 hours.- Depth drying.....±24 hours.
RECOMMENDED USE:	<p>The main function of “IMUNEUCE” is to protect and preserve the wood against the “wood bug” action.</p> <p>This function becomes fundamental when the wood is fair-faced, in case of beams and lathes presence in attics, wood for linings, or other similar situations. As it is manufactured in the brown and green color, it gives the possibility to transmit simultaneously to the wood a decorative effect and protection.</p>
SURFACE PREPARATION:	The wood surface has to be clean, dry, free of dirt, and with an absorption capacity.
APPLICATION:	<p>To mix well the product before to apply.</p> <p>The application is made with a paint-brush, in 1 or 2 coats without dilution, and in order to keep the wood well impregnated.</p> <p>After 48 hours, and in required situations, a varnishing with “NEUCELAC” can be effectuate.</p>
DILUTION:	This product is supplied ready to use.
COVERAGE:	Depending, more or less, on the wood absorption. As an orientation: 4 to 5 m ² /liter.
CLEAN-UP:	With “SYNTHETIC DILUENT”, right after the application.

WARNING:

- Inflammable product.
- In the case of a contact with the skin or the eyes, to wash with plenty of water and soap.
- Keep out of reach out children.
- For further information, the reading of our product **Safety Data Sheet** is essential.

**STORAGE
AND
PACKAGING:**

Packages should be kept properly closed, in good environmental conditions of temperature and humidity, and spend the product on the chronological order of supply.

Use it, with preference, up to 1 years after its manufactured date, but it can also be used after this date, as long as a good homogenization of the product can be verified.

It is supplied in packages of 1lt, 5lt, 20lt and 200 liters.