

29.01 – MARTELNEUCE

Air Drying Hammered Enamel

DESCRIPTION: Formulated with synthetic resins of quick drying, and metallic pigments of high quality, MARTELNEUCE is appropriated for the painting of metallic surfaces where a finish with a “hammered effect” is pretended.

FEATURES:

- Easy to apply and great adhesion.
- Good covering power.
- Quick drying and good hardness.
- Disguises small superficial imperfections.
- Develops a beautiful “hammered effect”.

SPECIFICATIONS:

- **Density**.....0,970±0,05
- **Viscosity**.....100 ± 15” Ford IV (20°C)
- **Color**.....Grey and others from the catalog
- **Finishing**.....Hammered.
- **Superficial drying**.....± 30 minutes.
- **Depth drying**.....± 2 hours.
- **VOC (volatile organic compound)**....^{a)} EU limit value set for this product cat. (A/i) 500 g/l (2010). This product contains a maximum of 499 g/l VOC.

RECOMMENDED USE: Due to its peculiar properties, MARTELNEUCE is for decorative painting of all the metallic surfaces. Its main field of application is in the painting industry of machines, metallic furniture, boxes for electrical switchboard, and other situations when a disguise of imperfections and a beautiful decorative aspect is needed.

SURFACE PREPARATION: The metallic surface has to be clean, dry, free of rust and other oxides, and properly degreased.

APPLICATION: To mix well the product before to use.
The application is made with a spray-gun, in 2 coats, properly diluted, in a period of 15 to 30 minutes.
The 1st coat is applied very fine (pulverization), in order to cover the bottom.
The 2nd coat is applied less diluted, in order to obtain the hammered finish.
When an anticorrosive protection is pretended, before applying the enamel, to apply a coat of “NEUCERAPID PRIMER”, which after dry should be sanded.

DILUTION: With “DILUENT 200”, to a maximum of 5%.



- COVERAGE:** On average and per coat: 8 to 10 m²/liter.
- CLEAN-UP:** With "DILUENT 200" or "CELLULOSE DILUENT", right after the application.
- WARNING:**
- Inflammable product. In the case of a contact with the skin or the eyes, to wash with plenty of water.
 - Toxic by inhalation or ingestion. In case of ingestion to call for a doctor.
- RECOMMENDATION S:** Do not apply the product with a very cold or humid weather. Good environmental conditions are the ideal.
- STORAGE AND PACKAGING:** Packages should be kept properly closed, in good environmental conditions of temperature and humidity, and spend the product on the chronological order of supply.
Use it, with preference, up to 2 years after its manufactured date, but it can also be used after this date, as long as a good homogenization of the product can be verified.
It is supplied in packages of 1lt, 5lt and 20 liters.

Note a) The value of the VOC previously mentioned concerns ready-to-use products, according to the technical specifications that we recommend. We do not take any responsibility for other mixtures made to the product. We draw special attention to all our agents for the responsibility that they take by not respecting what the Directive 2004/42/CE establishes.